



PRODUCT SPECIFICATION

AISCAN A

TYPE	COMPOSITION	Ø OUT mm	TOLERANCE mm	Ø INS. mm	LENGTH m	TOLER. mm	ENTRANCE	LENGTH ENTRANCE mm +-10%	LABELS	TUBES MALLET	Nº TIES
AISCAN-A-25	RIGID PVC	25	+0 -0,3	19	3000	+10 -5	1	30	1	25	3
AISCAN-A-32	RIGID PVC	32	+0 -0,4	26	3000	+10 -5	1	37	1	20	3
AISCAN-A-40	RIGID PVC	40	+0 -0,4	33	3000	+10 -5	1	40	1	10	3
AISCAN-A-50	RIGID PVC	50	+0 -0,5	42	3000	+10 -5	1	48	1	10	3
EDITION DATE	EDITION NUMBER	CARD NUMBER									
2014/05	3	EP-A									

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-21	
CODE:	222112540010
CRUSHING STRENGTH:	>320 N
IMPACT RESISTANCE:	>1J at -5°C
OPERATING TEMPERATURE RANGE:	-5+60°C
RIGID	YES
DIELECTRICAL RIGIDITY:	>2000 V
ISOLATION RESISTANCE:	>100 MOhm
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	NO
COLOUR:	BLACK

CHARACTERISTICS LABEL <i>Each label indicates:</i>
Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.
EACH TUBE BAR INDICATES: type, nominal, standard UNE-EN applied, code, date, hour, manufacture line and "CE" marked.

ACCESORY TUBE
TYPE "AISCAN-A"

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WITHOUT PREVIOUS ADVERTISMENT.