



PRODUCT SPECIFICATION

AISCAN BMPI - 35

TYPE	MATERIAL	COATING	A	B	ALLOWABLE WORKING LOAD (N/m)	PACKING (meters)	PLAIN	
AISCAN-BMPI-310	STAINLESS STEEL	-	100	35	365	12		
AISCAN-BMPI-315	"	-	150	35	356	12		
AISCAN-BMPI-320	"	-	200	35	405	12		
AISCAN-BMPI-330	"	-	300	35	405	6		
EDITION DATE	EDITION NUMBER	CARD NUMBER						
2013/10	2	EP-BMPI 35						

CHARACTERISTICS ACCORDING TO STANDARD IEC 61537:2006	
DESCRIPTION:	MESH CABLE TRAY STAINLESS STEEL.
COATING:	STAINLESS STEEL, AISI 304
MATERIAL:	METALLIC
ELECTRICAL CONTINUITY:	YES
FLAME PROPAGATE:	NO
OPERATING TEMPERATURE RANGE:	-40 °C / 150 °C
RESISTANCE TO CORROSION:	TYPE 9A
IMPACT RESISTANCE:	20 J TO -40 °C
ALLOWABLE WORKING LOAD (CTA):	DISTANCE BETWEEN SUPPORTS (1,5 METERS)

OBSERVATIONS
FOR THE UNION BETWEEN BRACKETS WILL BE REQUIRED THE USE OF 2 TO 4 SETS OF UNION (CUBS), DEPENDING THE WIDTH OF THE TRAY.
WITH ALL EDGES ROUNDED.
ACCESORIES
TRAY ATTACHMENT ASSEMBLY (CUB) UNIVERSAL MESH CABLE TRAY COVER (TUBC) OMEGA BRACKET (SO)

THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.