



PRODUCT SPECIFICATION

AISCAN BMPR - 35

TYPE	MATERIAL	COATING	A	B	ALLOWABLE WORKING LOAD (N/m)	PACKING (meters)	PLAIN
AISCAN-BMPR-310	METALLIC	ELECTRO ZINC PASSIVATED	60	60	367	12	
AISCAN-BMPR-315	"	"	100	60	3535	12	
AISCAN-BMPR-320	"	"	150	60	429	12	
AISCAN-BMPR-330	"	"	200	60	376	6	
EDITION DATE	EDITION NUMBER	CARD NUMBER					
2017/09	3	EP-BMPR 35					

CHARACTERISTICS ACCORDING TO STANDARD IEC 61537:2006	
DESCRIPTION:	MESH CABLE TRAY HIGH RESISTANCE
COATING:	IN ACCORDING TO UNE-EN 12329:2001
MATERIAL:	METALLIC
ELECTRICAL CONTINUITY:	YES
FLAME PROPAGATE:	NO
OPERATING TEMPERATURE RANGE:	-40 °C / 150 °C
RESISTANCE TO CORROSION:	CLASS 8
IMPACT RESISTANCE:	20 J TO -40 °C
ALLOWABLE WORKING LOAD (CTA):	DISTANCE BETWEEN SUPPORTS (1,5 METERS)

OBSERVATIONS
FOR THE UNION BETWEEN BRACKETS WILL BE REQUIRED THE USE OF 2 TO 4 SETS OF UNION (CUBS), DEPENDING THE WIDTH OF THE TRAY// OR UNIFAST ACCESORIES.
WITH ALL EDGES ROUNDED.
ACCESORIES
TRAY ATTACHMENT ASSEMBLY (CUB)
UNIFAST
UNIVERSAL MESH CABLE TRAY COVER (TUBC)
OMEGA BRACKET (SO)

THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.