



PRODUCT SPECIFICATION

AISCAN BMPZ - 100

TYPE	MATERIAL	COATING	A	B	ALLOWABLE WORKING LOAD (N/m)	PACKING (meters)	PLAIN	
AISCAN-BMPZ-1020	METALLIC	ELECTRO ZINC	200	100	1017	12		
AISCAN-BMPZ-1030	"	"	300	100	794	6		
AISCAN-BMPZ-1040	"	"	400	100	788	6		
AISCAN-BMPZ-1050	"	"	500	100	564	6		
AISCAN-BMPZ-1060	"	"	600	100	518	6		
EDITION DATE	EDITION NUMBER	CARD NUMBER						
2013/10	2	EP-BMPZ 100						

CHARACTERISTICS ACCORDING TO STANDARD IEC 61537:2006

DESCRIPTION:	MESH CABLE TRAY ELECTRO ZINC
COATING:	ELECTRO ZINC IN ACCORDING TO UNE-EN 12329:2001
MATERIAL:	METALLIC
ELECTRICAL CONTINUITY:	YES
FLAME PROPAGATE:	NO
OPERATING TEMPERATURE RANGE:	-40 °C / 150 °C
RESISTANCE TO CORROSION:	CLASS 6
IMPACT RESISTANCE:	20 J TO -40 °C
ALLOWABLE WORKING LOAD (CTA):	DISTANCE BETWEEN SUPPORTS (1,5 METERS)

OBSERVATIONS

FOR THE UNION BETWEEN BRACKETS WILL BE REQUIRED THE USE OF 2 TO 4 SETS OF UNION (CUBS), DEPENDING THE WIDTH OF THE TRAY.

WITH ALL EDGES ROUNDED.

ACCESORIOS

TRAY ATTACHMENT ASSEMBLY (CUB)
 UNIVERSAL MESH CABLE TRAY COVER (TUBC)
 OMEGA BRACKET (SO)

THE INSTALLATION OF THIS PRODUCT WILL BE CARRIED OUT ACCORDING TO THE R.E.B.T.