



PRODUCT SPECIFICATION

AISCAN CR

TYPE	COMPOSITION	ø OUT mm	TOLERANCE mm	ø INS. mm	LENGTH m	TOLER. mm	Nº SPIRAL	SPIRAL SEQUENCE	LAYERS	RADIUS MIN. CURVATURE mm	Nº TIES	
AISCAN-CR-16	MIXED PVC	16,5	+0,5	10,7	100	+2 -1	90	10-10-10-10-10-10-10-10-10	9	48	4	
AISCAN-CR-20	MIXED PVC	20,5	+0,5	13,4	100	+2 -1	76	8-9-8-9-8-9-8-9-8	9	60	4	
AISCAN-CR-25	MIXED PVC	25,5	+0,5	18,5	75	+2 -1	60	8-7-8-7-8-7-8-7	8	75	4	
AISCAN-CR-32	MIXED PVC	32,5	+0,5	24,3	50	+2 -1	35	5-5-5-5-5-5-5	7	96	4	
AISCAN-CR-40	MIXED PVC	40,5	+0,5	31,2	25	+1 -0,5	20	5-5-5-5	4	160	4	
AISCAN-CR-50	MIXED PVC	50,5	+0,5	39,6	25	+1 -0,5	20	5-5-5-5	4	200	4	
EDITION DATE	EDITION NUMBER	CARD NUMBER										
2016/06	9	EP-CR										

CHARACTERISTICS ACCORDING TO STANDARD UNE-EN 61386-22	
CODE:	232122540010
CRUSHING STRENGTH:	>320 N
IMPACT RESISTANCE:	>2J at -5°C
OPERATING TEMPERATURE RANGE:	-5+60°C
CURVABLE / TRANSVERSE ELASTIC	YES
DIELECTRICAL RIGIDITY:	>2000 V
ISOLATION RESISTANCE:	>100 MOhm
EXTERNAL INFLUENCES:	IP54
COLOUR:	BLACK
FLAME PROPAGATE:	NO

CHARACTERISTICS LABEL
<i>Each label indicates:</i>
Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WITHOUT PREVIOUS ADVERTISEMENT.-