



PRODUCT SPECIFICATION

UNDERGROUND CONDUITS FOR TELECOMMUNICATIONS - AISCAN

REF.	TYPE	COMPOSITION	Ø OUT mm	TOL. mm	THICKNESS TUBE mm	TOLER. mm	LONG. ROLL m	Ø INS. ROLL mm	Ø OUT. ROLL mm	SPIRAL SEQUENCE	LAYERS	WEIGHT Kgr.		
MT40X2.4S	SINGLE TUBE	POLYOLEFINE	40	+0.4 -0	2.4	+0.3 -0	500	1400	2000	8-8-8-8-8-8-8-4	9	150		
MT40X3S*	SINGLE TUBE	POLYOLEFINE	40	+0.4 -0	3	+0.3 -0	500	1400	2000	8-8-8-8-8-8-8-4	9	175		
BT40X2.4S	DOUBLE TUBE	POLYOLEFINE	40	+0.4 -0	2.4	+0.3 -0	500	1400	2200	8-8-8-8-8-8-8-8	8	290		
BT40X3S*	DOUBLE TUBE	POLYOLEFINE	40	+0.4 -0	3	+0.3 -0	500	1400	2200	8-8-8-8-8-8-8-8	8	360		
TT40X2.4S	TRIPLE TUBE	POLYOLEFINE	40	+0.4 -0	2.4	+0.3 -0	500	1400	2400	7-7-7-7-7-7-7-4	13	520		
TT40X3S*	TRIPLE TUBE	POLYOLEFINE	40	+0.4 -0	3	+0.3 -0	500	1400	2400	7-7-7-7-7-7-7-4	13	590		
CT40X3S-150*	FOURFOLD TUBE	POLYOLEFINE	40	+0.4 -0	3	+0.3 -0	150	1400	2200	5-5-5-5-5-2	5	210		
CT40X3S-300*	FOURFOLD TUBE	POLYOLEFINE	40	+0.4 -0	3	+0.3 -0	300	1400	2300	10-10-10-10-10-10-10-10-5	6	420		
EDITION DATE	EDITION NUMBER	CARD NUMBER												
2018/03	02	FT-TUB. TELEC.												

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-24

TUBE SILICONATED FOR TELECOMMUNICATIONS

*According to standard Iberdrola NI 52.95.20

CRUSHING STRENG:	>450 N
IMPACT RESISTANCE:	28 J
CURVABLE	YES
RESISTANCE TO INTERNAL PRESSURE. TUBE 3 mm.	12 atm.
RESISTANCE TO INTERNAL PRESSURE. TUBE 2.4 mm.	6 atm.
COLOUR:	GREEN

CHARACTERISTICS LABEL

Each label indicates:

Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

The tube is marked every 2 meters with a code indicating: brand, type and use.

ACCESORY TUBE

TYPE "AISCAN-BUCT"

