



PRODUCT SPECIFICATION

AISCAN TEI

TYPE	COMPOSITION	Ø OUT mm	TOLER- ANCE mm	Ø INS. mm	LENGTH m	TOLER. mm	Nº SPIRAL	SPIRAL SEQUENCE	LAYERS	RADIUS MIN. CURVATURE mm	Nº TIES
AISCAN-TEI-16	RIGID PVC	16	+0 -0,3	10,0	100	+2 -1	94	11-10-11-10-11-10-11-10-10	9	48	4
AISCAN-TEI-20	RIGID PVC	20	+0 -0,3	13,4	100	+2 -1	77	9-8-9-8-9-8-9-8-9	9	60	4
AISCAN-TEI-25	RIGID PVC	25	+0 -0,4	18,5	75	+2 -1	56	8-8-8-8-8-8-8	7	75	4
AISCAN-TEI-32	RIGID PVC	32	+0 -0,4	24,3	50	+2 -1	39	7-6-7-6-7-6-6	6	96	4
AISCAN-TEI-40	RIGID PVC	40	+0 -0,4	31,2	25	+1 -0,5	20	5-5-5-5	4	160	4
AISCAN-TEI-50	RIGID PVC	50	+0 -0,5	39,6	25	+1 -0,5	18	4-3-4-3-4	5	200	4
EDITION DATE	EDITION NUMBER	CARD NUMBER									
2014/05	11	EP-TEI									

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-22

CODE:	332122540010
CRUSHING STRENGTH:	>750 N
IMPACT RESISTANCE:	>2J at -5°C
OPERATING TEMPERATURE RANGE:	-5+60°C
CURVABLE	YES
DIELECTRICAL RIGIDITY:	>2000 V
ISOLATION RESISTANCE:	>100 MOhm
EXTERNAL INFLUENCES:	IP54
FLAME PROPAGATE:	NO
COLOUR:	GREY RAL. 7035

WITH BUILT-IN STEEL GUIDE

CHARACTERISTICS LABEL

Each label indicates:

Type, nominal, number of meter, standard UNE-EN applied, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.

ACCESORY TUBE

TYPE "AISCAN-MP" C/ GREY

- NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WITHOUT PREVIOUS ADVERTISMENT.-