




PRODUCT SPECIFICATION

AISCAN UV

TYPE	COMPOSITION	Ø OUT mm	TOLERA NCE mm	Ø INS. mm	LENGTH m	TOLER. mm	Nº SPIRAL	SPIRAL SEQUENCE	LAYERS	RADIUS MIN. CURVATURE mm	Nº TIES	IMPACT RESISTANCE AT −5°C. (J) *	
AISCAN-UV-40	POLYOLEFINE	40	+0 -0,4	30,5	100	+2 -1	55	11-11-11-11-11	5	160	4	15	
AISCAN-UV-50	“	50	+0 -0,5	40	100	+2 -1	48	8-8-8-8-8-8	6	200	4	15	
AISCAN-UV-63	“	63	+0 -0,6	50	100	+2 -1	40	8-8-8-8-8	5	252	6	20	
AISCAN-UV-90	“	90	+1,7 -0	73	75	+2 -1	28	6-5-6-5-6	5	252	6	20	
AISCAN-UV-110	“	110	+2 -0	88	50	+1,5 -1	17,6	5-4-5-3+4/6	4	252	6	28	
AISCAN-UV-160	“	160	+2,9 -0	130	50	+1,5 -1	14,2	4-3-4-3-4+1/6	4	400	6	40	
EDITION DATE	EDITION NUMBER	CARD NUMBER											
2015/10	1	EP-UV											

CHARACTERISTICS ACCORDING TO STANDARD IEC 61386-24	
MULTIPLE WALL TUBE (Inside smooth, outside corrugated)	
TYPE: N (Normal)	
CRUSHING STRENGTH:	>450 N
IMPACT RESISTANCE:	Normal*
CURVABLE	YES
EXTERNAL INFLUENCES:	IP54
COLOUR:	BLACK
UV RESISTANT	YES

CHARACTERISTICS LABEL
<i>Each label indicates:</i>
Type, nominal, number of meter, standard UNE-EN applied, use light, "CE" marked, storage and use instructions, Bar code EAN-13, date, control number and manufacture line.
The tube goes marking every 2 meters with a code that indicates: brand, type, nominal and use.

ACCESSORY TUBE
TYPE "AISCAN-MP"

ACCORDING TO STANDARD UNE-EN 60754-2 about "Determination of the degree of acidity of gases for materials by measuring pH and conductivity".

WITH NYLON GUIDE INCLUDED

NO CONTROLLED COPY. THIS INFORMATION COULD BE MODIFIED BY AISCAN WITHOUT PREVIOUS ADVERTISEMENT.